

150 square plaster-in gimbal










A 150mm square recessed directional gimbal luminaire with absolute minimal visual impact.

Applications:

- Where the ceiling is to be plastered or re-plastered with a gypsum finish.

Features:

- 30° tilt in all directions.
- Insert is interchangeable between lamp types and fixed downlights.
- Tool free 'easy click' second fix insert.
- Tool free 'easy click' lamp and gear maintenance.
- Internal cartridges with pre-wired plug connectors for efficient installation.
- Frosted glass lens, coloured dichroic glass filter and louvre system available.

code	lamp	type	base	(1) watts	(1) lumen / cd	cut-out
P150SRG-LVAR111	 Low voltage metal reflector	AR111	G53	35-100W	8500 (24°) lm	170 x 170 mm
P150SRG-LEDR111	 LED metal reflector	LEDR111	G53	-	-	170 x 170 mm
P150SRG-CDM-TC	 Ceramic discharge metal halide	CDM-TC	G8.5	35-70W	2200-6000 lm	170 x 170 mm
P150SRG-CDMR111	 Ceramic discharge metal reflector	CDMR111	GX8.5	35-70W	4225 (24°) lm	170 x 170 mm
P150SRG-LED-XI-830-700 *	 Xicato XSM-700	LED	-	12.4W	700 lm	170 x 170 mm
P150SRG-LED-XI-830-1000	 Xicato XSM-1000	LED	-	18.3W	1000 lm	170 x 170 mm
P150SRG-LED-XI-930-700	 Xicato XSM-700A	LED	-	15W	700 lm	170 x 170 mm

Notes:

- Indicative lamp information shown. Consult lamp manufacturer for current information.
 - Glass and louvre available, please see page 185 for details.
 - LED specification subject to change. Please contact us for latest info.
 - Not all lamps allow full 360 degree tilt rotation.
 - Xicato LED has a 25° beam angle (13° and 35° beam angle also available)
 - Code marked "*" shows Xicato stock item

Other information:

Important information	Page 181
Dimming	Page 182
Accessories	Page 185

