

# 300 square plaster-in gimbal










A 300mm square recessed directional multiple head gimbal luminaire with absolute minimal visual impact.

### Applications:

- Where the ceiling is to be plastered or re-plastered with a gypsum finish.

### Features:

- 30° tilt in all directions.
- Insert is interchangeable between lamp types and fixed downlight.
- Four individual tool free 'easy click' second fix insert.
- Tool free 'easy click' lamp and gear maintenance.
- Internal cartridges with pre-wired plug connectors for efficient installation.
- Frosted glass lens, coloured dichroic glass filter and louvre system available.

code	lamp	type	base	(1) watts	(1) lumen / cd	cut-out
P300SRG4-LEDR111	 LED metal reflector	LEDR111	G53	-	-	320 x 320 mm
P300SRG4-LVAR111	 Low voltage reflector	AR111	G53	max 100W x 4	8500 lm (24°) x 4	320 x 320 mm
P300SRG4-CDMR111	 Ceramic discharge metal reflector	CDMR111	GX8.5	35-70W x 4	15000 lm (24°) x 4	320 x 320 mm
P300SRG4-CDM-TC	 Ceramic discharge metal halide	CDM-TC	G8.5	35-70W x 4	2800 lm (24°) x 4	320 x 320 mm
P300SRG4-LED-XI-830-700*	 Xicato XSM-700	LED	-	12.4W	700 lm x 4	320 x 320 mm
P300SRG4-LED-XI-830-1000	 Xicato XSM-1000	LED	-	18.3W	1000 lm x 4	320 x 320 mm
P300SRG4-LED-XI-930-700	 Xicato XSM-700A	LED	-	15W	700 lm x 4	320 x 320 mm

### Notes:

- Indicative lamp information shown. Consult lamp manufacturer for current information.
  - Glass and louvre available, please see page 185 for details.
  - LED specification subject to change. Please contact us for latest info.
  - Not all lamps allow full 360 degree tilt rotation.
  - Xicato LED has a 25° beam angle (13° and 35° beam angle also available)
  - Code marked "\*" shows Xicato stock item

### Other information:

Important information	Page 181
Dimming	Page 182
Accessories	Page 185

