

60 Square Downlight LED

whitegoods

Project Title:

Luminaire Ref:



plaster-in



bezel



Specifier Details

| Ordering Information | | | | | | | |
|-------------------------|--------------------|----------------------|-------------------|----------------------|----------------------|----------|---------|
| Frame | LED ¹ | Rated Lumens | Beam ^o | Voltage ² | Power Supply | Diffuser | Options |
| WG-P60SDL plaster-in | 80 CRI XTD-827 | 1300 9.5W | 38° 54° | STD UNV | X S | CG FG | EM |
| | XTD-830 | 965 | | | | | |
| WG-B60SDL bezel trim | XTD-835 | 6.6W | 38° 54° | STD UNV | D010 D110 DALI | FR MP | EM |
| | 95 CRI XTD-927 | 1300 13.3W | | | | | |
| | XTD-930 | 965 | | | | | |
| | XTD-935 XTD-940 | 9.2W | | | | | |

For North America specification please visit inter-lux.com/products/60-square-downlight/

Luminaire

- Bezel trim or trimless 'plaster-in'.
- Installation from below for refurbishment or new construction.
- Twist lock diecast aluminium lamp insert module.
- Heavy gauge steel trim housing.
- Tool free lamp maintenance.
- Open aperture standard, other diffusers available (see diffusers).
- Powder coat painted white - RAL 9010.
- Cut Out = 70 x 70mm
- Luminaires rated at 40° maximum ambient temperature.

LED¹

Xicato XTM 80 Series, 80 CRI

- XTD-827 = 2700K
- XTD-830 = 3000K
- XTD-835 = 3500K
- XTD-840 = 4000K

Xicato ATM Artist Series, 95 CRI

- XTD-927 = 2700K
- XTD-930 = 3000K
- XTD-935 = 3500K
- XTD-940 = 4000K

Rated Lumens³

Xicato XTM 80 Series

- 1300 = 1300 lm @ 700mA, 9.5W
- 965 = 965 lm @ 500mA, 6.6W

Xicato XTM Artist Series

- 1300 = 1300 lm @700mA, 13.3W
- 965 = 965 lm @500mA, 9.2W

Beam^o

- 38 = 38° accent illumination
- 54 = 54° general illumination

Voltage²

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

Power Supply (remote)

- X = No driver (to be supplied separately)
- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

Diffuser (open aperture standard)

- CG = regressed clear glass
- FG = flush frosted diffuser
- FR = regressed frosted diffuser
- MP = regressed micro prismatic glass

Options

- EM = Contact factory for emergency lighting options

Notes

- 1 Other lumen packages available, consult factory.
- 2 For specification of Whitegoods products in North America please visit inter-lux/whitegoods
- 3 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.

