

# 60 Square Downlight LED (IP)

whitegoods

Project Title: .....

Luminaire Ref: .....



plaster-in



bezel



## Specifier Details

Ordering Information							
Frame	LED <sup>1</sup>	Rated Lumens	Beam <sup>o</sup>	Voltage <sup>2</sup>	Power Supply	Diffuser	Options
WG-P60SDLIP plaster-in	80 CRI XTD-827	<b>1300</b> 9.5W	38° 54°	STD UNV	X S	CG MP	EM
	XTD-830	<b>965</b>					
WG-B60SDLIP bezel trim	XTD-835	6.6W			D010 D110 DALI		
	XTD-840						
	95 CRI XTD-927	<b>1300</b> 13.3W					
	XTD-930	<b>965</b>					
	XTD-935	9.2W					
	XTD-940						

For North America specification please visit [inter-lux.com/products/60-square-downlight/](http://inter-lux.com/products/60-square-downlight/)

### Luminaire

- Bezel trim or trimless 'plaster-in'.
- IP65 rated, wet location (suitable for shower).
- Installation from below for remodel or new construction.
- Machined diecast aluminum lamp insert module with retaining springs and gasket.
- Heavy gauge steel trim housing.
- Tool free lamp maintenance.
- Frosted regressed diffuser standard, other diffusers available (see diffusers).
- Cut Out = 70 x 70mm
- Luminaires rated at 40° maximum ambient temperature.

### LED<sup>1</sup>

Xicato XTM 80 Series, 80 CRI

- XTD-827 = 2700K
- XTD-830 = 3000K
- XTD-835 = 3500K
- XTD-840 = 4000K

Xicato XTM Artist Series, 95 CRI

- XTD-927 = 2700K
- XTD-930 = 3000K
- XTD-935 = 3500K
- XTD-940 = 4000K

### Rated Lumens<sup>3</sup>

Xicato XTM 80 Series

- 1300 = 1300 lm @ 700mA, 9.5W
- 965 = 965 lm @ 500mA, 6.6W

Xicato XTM Artist Series

- 1300 = 1300 lm @700mA, 13.3W
- 965 = 965 lm @500mA, 9.2W

### Beam<sup>o</sup>

- 38 = 38° accent illumination
- 54 = 54° general illumination

### Voltage<sup>2</sup>

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

### Power Supply (remote)

- X = No driver (to be supplied separately)
- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

### Diffuser (regressed frosted standard)

- CG = regressed clear glass
- MP = regressed micro prismatic glass

### Options

- EM = Contact factory for emergency lighting options

### Notes

- 1 Other lumen packages available, consult factory.
- 2 For specification of Whitegoods products in North America please visit [inter-lux/whitegoods](http://inter-lux/whitegoods)
- 3 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.



Whitegoods reserves the right to make technical alterations without notice.  
w: [www.whitegoods.com](http://www.whitegoods.com) e: [info@whitegoods.com](mailto:info@whitegoods.com)

(930-20196-REVA)