

60 Square Ceiling / Floor Wash LED

whitegoods

Project Title:


Luminaire Ref:




Plaster-in



Bezel



Plaster-in



Bezel

Ordering Information					
Frame	LED ¹	Rated Lumens	Voltage ²	Power Supply	Options
WG-P60SCFW plaster-in	80 CRI CL-827	3.2W 314	STD UNV	X S	EM
WG-B60SCFW bezel trim	CL-830 CL-835 CL-840	335 346 351		D010 D110 DALI	

For North America specification please visit inter-lux.com/products/60-square-ceiling-floor-wash/

Luminaire

- Bezel trim or trimless 'plaster-in' square ceiling or floor washer for drywall.
- Installation from room side of the wall for remodel or new construction.
- 'Easy click' tool free installation of diecast aluminum lamp insert module.
- Heavy gauge steel trim housing.
- Regressed frosted glass lens standard.
- Powder coat painted white - RAL 9010.

LED¹

LED Citizen, 80 CRI

- CL-827-314 = 2700K
- CL-830-335 = 3000K
- CL-835-346 = 3500K
- CL-840-351 = 4000K

Rated Lumens

- 314 = 314lm @ 350mA, 3.2W, 2700K
- 335 = 335lm @ 350mA, 3.2W, 3000K
- 346 = 346lm @ 350mA, 3.2W, 3500K
- 340 = 340lm @ 350mA, 3.2W, 4000K

Voltage²

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

Power Supply (remote)

- X = No driver (to be supplied separately)
- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

Options

- EM = Contact factory for emergency lighting options.

Notes

- 1 Other lumen packages available, consult factory.
- 2 For specification of Whitegoods products in North America please visit interlux/whitegoods
- 3 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.

Specifier Details