

Mini Edgeless Cove LED


whitegoods

Project Title:

Luminaire Ref:



Plaster-in



Ordering Information

Frame	Type	Length	LED ¹	Color ²	Voltage ³	Power	Diffuser	Mount	Options ⁵
WG-MEC	S	A	L	827	STD	S	S (std)	P	LEC REC LREC LWR RWR DL
	PC	A x B	M	830	UNV	D010	OF		
	PR	A x B x C	H	835		D110	SF		
	PZ	A x B x A x B	927	DALI					
			930						
			935						
940									

For North America specification please visit inter-lux.com/products/mini-edgeless-cove-led/

Luminaire

- Indirect cove system featuring clean box profile for continuous lighting inside coves or as stand alone cove system.
- White LED light source.
- Lengths and angles factory cut to exact field dimensions.
- Powder coat painted white - RAL 9010.
- Snap-on satin diffuser optimized for forward distribution (standard).

Type

- S = Straight run
- PC = Standard patterns coffer 2, 3 or 4sided with 90° corners
- PR = Standard patterns raft 2, 3 or 4sided with 90° corners
- PZ = Non-standard patterns and/or corners other than 90°, consult factory

Length

- A, B, C = specify millimetres to the nearest 1mm (i.e. 5000mm) For pattens specify each length (i.e. 2 sided: A x B = 605mm x 305mm; 3 sided: A x B x C; 4 sided: A x B x A x B)

LED¹

- L = Low Power (10W/m)
- M = Mid Power (20W/m)
- H = High Power (33W/m)

Color / Lumens²

80+ CRI minimum (Low/Mid/High)

- 827 = 2700K, 771/1433/2266 lm/m
- 830 = 3000K 771/1433/2266 lm/m
- 835 = 3500K, 771/1492/2358 lm/m
- 840 = 4000K, 817/1850/2404 lm/m
- For 90+ CRI specify 927, 930, etc.

Voltage³

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

Power Supply (remote)

- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

Diffuser

- S = Snap-on satin diffuser (standard)
- OF = Opal flat diffuser
- SF = Satin flat diffuser

Mounting

- P = plaster-in

Options⁵

- LEC = Left end cap
- REC = Right end cap.
- LREC = Left & Right end caps
- LWR = Left wall return
- RWR = Right wall return
- DL = Damp location

Notes

- 1 Wattage shown does not include power supplies/drivers.
- 2 Delivered lumens with snap-on satin diffuser shown. Lumens for CRI 90(+), is about 16% lower compared to standard CRI 80(+).
- 3 For specification of Whitegoods products in North America please visit interlux.com/products/mini-edgeless-cove-led/
- 4 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.
- 5 To specify multiple options select the appropriate grouped codes from the dropdown e.g.. LEC-DL.

Specifier Details