


Project Title:

Luminaire Ref:



Plaster-in



Ordering Information

Frame	Type	Length	LED ¹	Color ²	Voltage ³	Power	Diffuser	Mount	Options
WG-MZC20L	S	A	L	827	STD	S	OD (std)	P	C4 (std) C10 C20 C30 DL
	PC	A x B	M	830	UNV	D010	SD		
	PR	A x B x C		835		D110			
	PZ	A x B x A x B		840		DALI			
				927					
				930					
				935					
			940						

For North America specification please visit inter-lux.com/products/mini-z-led/

Luminaire

- Miniature continuous perimeter light with knife edge detail.
- White LED light source.
- Standard Opal Diffuser for even illumination and no LED appearance. Satin Diffuser for high efficiency and minimal LED appearance.
- Lengths and angles factory cut to exact field dimensions.
- Powder coat painted white - RAL 9010.

Type

- S = Straight run
- PC = Standard patterns coffer 2, 3 or 4sided with 90° corners
- PR = Standard patterns raft 2, 3 or 4sided with 90° corners
- PZ = Non-standard patterns and/or corners other than 90°, consult factory

Length

- A, B, C = specify millimetres to the nearest 1mm (i.e. 5000mm) For pattens specify each length (i.e. 2 sided: A x B = 605mm x 305mm; 3 sided: A x B x C; 4 sided: A x B x A x B)

LED¹

- L = Low Power (10W/m)
- M = Mid Power (20W/m)

Color / Lumens²

- 80+ CRI minimum (Low/Mid)
- 827 = 2700K, 1037/1752 lm/m
 - 830 = 3000K, 1125/1900 lm/m
 - 835 = 3500K, 1125/1900 lm/m
 - 840 = 4000K, 1165/1972 lm/m
 - For 90+ CRI specify 927, 930, etc.

Voltage³

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

Power Supply (remote)

- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

Diffuser

- OD = Opal diffuser (standard)
- SD = Satin diffuser

Mounting

- P = plaster-in

Options

- C4 = 1220mm tray cable (standard)
- C10 = 3000mm tray cable.
- C20 = 6000mm tray cable
- C30 = 9000mm tray cable
- DL = Damp location

Notes

- 1 Wattage shown does not include power supplies/drivers.
- 2 Delivered lumens with satin diffuser shown. Lumens for CRI 90(+), is about 16% lower compared to standard CRI 80(+).
- 3 For specification of Whitegoods products in North America please visit interlux/whitegoods
- 4 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.

Specifier Details