


# 100 Round Angled Gimbal 45 LED



whitegoods

Project Title: .....

Luminaire Ref: .....



plaster-in



## Specifier Details

Ordering Information							
Frame	LED <sup>1</sup>	Rated Lumens	Beam°	Voltage <sup>2</sup>	Power Supply	Accessories	Options
WG-P100RAG45 plaster-in	80 CRI XTD-827 XTD-830 XTD-835 XTD-840	<b>1300</b> 9.5W <b>965</b> 6.6W	38 54	STD UNV	S D010 D110 DALI	AL AS CG FR MP	EM
	95 CRI XTD-927 XTD-930 XTD-935 XTD-940	<b>965</b> 9.2W					

For North America specification please visit [inter-lux.com/products/100-round-angled-gimbal-45/](http://inter-lux.com/products/100-round-angled-gimbal-45/)

### Luminaire

- Trimless 'plaster-in' oval angled gimbal for drywall ceilings with 45° tilt.
- 30° adjustable lamp insert standard.
- Installation from below for remodel or new construction. 'Easy click' tool free installation of diecast aluminum lamp insert module.
- Diecast aluminum trim housing with heavy gauge galvanized steel yoke with removable jbox from below ceiling.
- Pre-wired with a 'Plug and Play' electrical connection.
- Open aperture standard, accessories available. Powder coat painted white - RAL 9010.

### LED<sup>1</sup>

Xicato XTM 80 Series, 80 CRI

- XTD-827 = 2700K
- XTD-830 = 3000K
- XTD-835 = 3500K
- XTD-840 = 4000K

Xicato XTM Artist Series, 95 CRI

- XTD-927 = 2700K
- XTD-930 = 3000K
- XTD-935 = 3500K
- XTD-940 = 4000K

### Rated Lumens<sup>3</sup>

Xicato XTM 80 Series, 80 CRI

- 1300 = 1300 lm @ 700mA, 9.5W
- 965 = 965 lm @ 500mA, 6.6W

Xicato XTM Artist Series, 95 CRI

- 965 = 965 lm @ 500mA, 9.2W

### Beam°

- 38 = 38° accent illumination
- 54 = 54° general illumination

### Voltage<sup>2</sup>

- STD = 220-240V
- UNV = 120-277V (excludes N. America)

### Power Supply (remote)

- S = Standard driver, non-dimming
- D010 = 0-10V dimming, min 1%
- D110 = 1-10 Volt dimming, min 1%
- DALI = DALI protocol, min 1%

### Accessories (open aperture standard)

- AL = hex louver
- AS = snoot
- CG = regressed clear glass
- FR = regressed frosted diffuser
- MP = regressed micro prismatic glass

### Options

- EM = Contact factory for emergency lighting options.

### Notes

- 1 Other lumen packages available, consult factory.
- 2 For specification of Whitegoods products in North America please visit [inter-lux/whitegoods](http://inter-lux/whitegoods)
- 3 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.

