

# 20 Linear Under Cabinet


whitegoods

Project Title: .....

Luminaire Ref: .....



Surface Mounted



## Ordering Information

Frame	Type	Length	LED <sup>1</sup>	Color <sup>2</sup>	Voltage <sup>4</sup>	Power	Diffuser	Mount	Options
WG-UC20LDL	S	300	L	827	STD	S	OD (std) SD	MM CM	W
		600	M	830	UNV				
		900		835					
		1200		840					
				927					
				930					
		935							
		1200		940					

For North America specification please visit [inter-lux.com/products/20-linear-under-cabinet-led/](http://inter-lux.com/products/20-linear-under-cabinet-led/)

### Luminaire

- Under cabinet and task light.
- Standard Opal Diffuser for even illumination and no LED appearance. Satin Diffuser for high efficiency and minimal LED appearance.
- Field replaceable LED boards.
- 80+ CRI, 3 steps MacAdam.
- Anodized aluminum finish standard. Optional white finish.
- On / Off switch with 3000mm cable and plug, standard.
- Luminaires rated at 40° maximum ambient temperature.

### Type

- S = Straight run (For other product configurations see SM20.)

### Length

- 300 = 325mm
- 600 = 625mm
- 900 = 925mm
- 1200 = 1225mm

### LED<sup>1</sup>

- L = Low Power (10W/m)
- M = Mid Power (20W/m)

### Color / Lumens<sup>2</sup>

- 80+ CRI minimum (Low)
- 827 = 2700K, 1037 lm/m
  - 830 = 3000K 1125 lm/m
  - 835 = 3500K 1125 lm/m
  - 840 = 4000K, 1165 lm/m
  - For 90+ CRI specify 927, 930, etc.

### Voltage<sup>4</sup>

- UNV = 120-277V (excludes N. America)

### Power Supply (remote)

- S = Standard driver, non-dimming

### Diffuser

- OD = Opal diffuser (standard)
- SD = Satin diffuser

### Mounting

- MM = magnetic mounting
- CM = clip mounting

### Options

- W = white finish

## Notes

- 1 Wattage shown does not include power supplies/drivers.
- 2 Delivered lumens with satin diffuser shown. Lumens for CRI 90(+), are about 16% lower compared to standard CRI 80(+).
- 3 24V fixture supplied complete with individual socket mount power supply 120-240V, 50-60 Hz and feed cable.
- 4 For specification of Whitegoods products in North America please visit [interlux.com/whitegoods](http://interlux.com/whitegoods)
- 5 Manufacturer LED module detail shown. Refer to photometry data for delivered lumens (LM79-08 results) on the Whitegoods website.

## Specifier Details