

100 Round Wall Wash Recessed Gimbal LED

whitegoods

Project Title:

Luminaire Ref:



Press to send

Send form to whitegoods



plaster-in

Ordering Information

Code	Module	Beam °	Diffuser	Driver	Voltage	Emergency
P100RWWG* plaster-in	XI-830-780* 80 CRI 8.8W 780 lm	Xicato 40°* degree	OA* open aperture (see accessories for available options)	ND non-dim 0-10V 0-10 Volt dim 1-10V 1-10 Volt dim TR trailing edge dim DALI DALI protocol	220-240V standard 120-277V universal	EMND non-dim EMST self-test EMDA DALI
	XI-930-500* 95 CRI 8.5W 500	Xicato 56° degree				
	CL-830-1300 80 CRI 13.6W 1360 lm	Citiled 19°* degree 41°* degree				

* Items available for Quickship

Product Description

100mm oval recessed luminaire trimless 'plaster-in' for absolute minimal visual impact. Available with recessed gimbal system.

Module

Example code: XI-830-1070

XI = Xicato / CL = Citizen
830 = 80CRI with 3000 Kelvin
1070 = 1070 lumen

Module: XI-827 / 830 / 840
780 lm running at 8.8W

Module Artist: XI-927 / 930 / 940
500 lm running at 8.5W
Xicato Artist LED are 95CRI

Module: CL-827 / 830 / 835 / 840
1360 lm running at 13.6W

Cut-out

Ø 120-170 mm

Accessories

AC-50-F: frosted glass
AG-50-C: clear glass
AG-50-S: sculpture glass
AG-50-P: micro prismatic glass
AL-50: louvre
AS-50: snoot

Driver

- ND: non-dimming
- 0-10V: 0-10 Volt dimming, min 0.1%
- 1-10V: 1-10 Volt dimming, min 10%
- TR: trailing edge dimming
- DALI: DALI protocol, min 10%

All drivers are suitable for remote mounting up to 10 meters from fixture. Longer distances are available on request.

Voltage

220-240V AC 50-60Hz
120-277V universal AC 50-60Hz

Emergency

EMND: emergency non-dimmable
EMST: emergency self-test
EMDA: emergency DALI protocol




Finish

Standard product finish is white powder coated RAL 9010 with 30% gloss.

Note

- Indicative LED information shown. Refer to photometry data for typical results.
- All LED modules available in 2700, 3000, 3500 and 4000 Kelvin.
- Xicato and Citiled modules can be underrun.
- Luminaires rated at 40°C maximum ambient temperature.
- 30° tilt in all directions.
- Insert with Citiled module must be disengaged in tilted position.

Please contact Whitegoods for further LED specifications.



Specifier Details

