

100 Square Wall Wash Recessed Gimbal

whitegoods

Project Title:

Luminaire Ref:

Press to send
Send form to whitegoods



plaster-in

Ordering Information

Code	Module	Diffuser	Driver	Voltage	Emergency
P100SWWG* plaster-in	LEDR/LVR* low voltage reflector LEDR/MVR* mains voltage reflector CDMR* ceramic metal halide	OA* open aperture (see accessories for available options)	ND non-dim 1-10V 1-10 Volt dim TR* trailing edge dim DALI DALI protocol DSI Digital	220-240V standard 120 - 277V universal	EMND non-dim

* Items available for Quickship

Product Description

100mm square recessed luminaire trimless 'plaster-in' for absolute minimal visual impact. Available with recessed gimbal system.

Lamp

LEDR/LVR: LED/Low Voltage Reflector

Type: MR16

Base: GU5.3

Lamp power: max 50W

Lamp lumens: 1000-2850 lm

LEDR/MVR: LED/Mains Voltage Reflector

Type: MR16

Base: GU10

Lamp power: max 50W

Lamp intensity: 200-1100 cd

CDMR: Ceramic Metal Halide Reflector (supermini)

Type: MR16

Base: GX20

Lamp power: max 50W

Lamp intensity: 1500-20000 cd

Cut-out

120 x 170 mm

Accessories

Accessories are only available when open aperture option is selected

AC-50-F: frosted glass

AG-50-C: clear glass

AG-50-S: sculpture glass

AG-50-P: micro prismatic glass

AL-50: louvre

AS-50: snoot

Power Supply

- ND: non dimming
- 1-10V: 1-10 Volt dimming, min 10% (low voltage only)
- TR: trailing edge dimming (excludes ceramic metal halide)
- DALI: DALI protocol, min 10% (low voltage only)
- DSI: Digital (low voltage only)

Voltage

220-240V AC 50-60Hz




120-277V universal AC 50-60Hz

Emergency

EMND: emergency non-dimmable (low voltage only)

Note

- Indicative lamp information shown. Consult lamp manufacturer for current information.
 - 30° tilt in all directions.
- Please contact Whitegoods for further lamp specifications.



Specifier Details

