

# 60 Round Directional Wall Wash

whitegoods

Project Title: .....

Luminaire Ref: .....



plaster-in

Ordering Information					
Code	Lamp	Diffuser	Driver	Voltage	Emergency
<b>P60RWWG*</b> plaster-in	<b>LEDL/LVR*</b> low voltage reflector <b>LEDL/MVR*</b> mains voltage reflector <b>CDMR*</b> ceramic metal halide	<b>OA*</b> open aperture (see accessories for available options)	<b>ND</b> non-dim <b>1-10V</b> 1-10 Volt dim <b>TR</b> trailing edge dim <b>DALI</b> DALI protocol <b>DSI</b> Digital	<b>220-240V</b> standard <b>120 - 277V</b> universal	<b>EMND</b> non-dim

\* Items available for Quickship

## Product Description

60mm oval recessed luminaire with trimless 'plaster-in' for absolute minimal visual impact. Available with a directional luminaire system.

## Lamp

LEDL/LVR: LED/Low Voltage Reflector  
Type: MR16  
Base: GU5.3  
Lamp power: max 50W  
Lamp lumens: 1000-2850 lm

LEDL/MVR: LED/Mains Voltage Reflector  
Type: MR16  
Base: GU10  
Lamp power: max 50W  
Lamp intensity: 200-1100 cd

CDMR: Ceramic Metal Halide Reflector (supermini)  
Type: MR16  
Base: GX20  
Lamp power: max 50W  
Lamp intensity: 1500-20000 cd

## Cut-out

oval  $\emptyset$  75 x 80 mm

## Accessories

AG-50-C: clear glass  
AG-50-S: sculpture glass  
AG-50-P: micro prismatic glass

## Driver

- ND: non dimming
- 1-10V: 1-10 Volt dimming, min 10% (low voltage only)
- TR: trailing edge dimming (excludes ceramic metal halide)
- DALI: DALI protocol, min 10% (low voltage only)
- DSI: Digital (low voltage only)

## Voltage

220-240V AC 50-60Hz.  
120-277V universal AC 50-60Hz.

## Emergency

EMND: emergency non-dimmable (low voltage only)


## Finish

Standard product finish is white powder coated RAL 9010 with 30% gloss.

## Note

- Indicative lamp information shown. Consult lamp manufacturer for current information.
- Lamp is recessed 30mm back from the ceiling.
- Recessed depth required is 110mm for LVR and MVR lamps, 170mm for CDM and emergency.
- Fix angle at 20°
- 170mm recess depth is required for CMH lamps and emergency.

Please contact Whitegoods for further lamp specifications.



Specifier Details