

150 Linear Surface Mounted and Suspended

whitegoods

Project Title:

Luminaire Ref:



surface mount



suspended

Ordering Information				
Code	Length mm	Power Supply	Voltage	Emergency
SM150L surface mount	600 standard length	ND non-dim 1-10V 1-10 Volt dim DALI DALI protocol DSI Digital	220-240V* standard 120 - 277V universal	EMND non-dim EMST self-test EMDA DALI
SP150L suspended	900mm standard length			
	1200mm standard length			
	1500mm standard length			
	1800mm standard length			
	2400mm standard length			
	Specify length			

* Items available for Quickship

Product Description

A 150mm linear recessed luminaire with bezel trim or trimless 'plaster-in' for absolute minimal visual impact.

Lamp

T5 fluorescent
Base: G5
Lamp power: 2 x 14W
Lamp lumens: 2400 lm
Information shown based on twin lamp configuration.

Power Supply

- ND: non dimming
- 1-10V: 1-10 Volt dimming, min 10%
- DALI: DALI protocol, min 10%
- DSI: Digital

Voltage

220-240V AC 50-60Hz
120-277V universal AC 50-60Hz

Emergency



EMND: emergency non-dimmable
EMST: emergency self-test
EMDA: emergency DALI protocol

Finish

Standard product finish is white powder coated RAL 9010 with 30% gloss.

Note

Indicative lamp information shown. Consult lamp manufacturer for current information.



Specifier Details