

# 60 Linear Surface Mounted and Suspended

whitegoods

Project Title: .....

Luminaire Ref: .....



surface mount



suspended

## Ordering Information

Code	Length mm	Power Supply	Voltage	Emergency
<b>SM60L</b> surface mount	<b>600</b> standard length	<b>ND*</b> non-dim <b>1-10V</b> 1-10 Volt dim <b>DALI</b> DALI protocol <b>DSI</b> Digital	<b>220-240V*</b> standard <b>120 - 277V</b> universal	<b>EMND</b> non-dim <b>EMST</b> self-test <b>EMDA</b> DALI
<b>SP60L</b> suspended	<b>900mm</b> standard length			
	<b>1200mm</b> standard length			
	<b>1500mm</b> standard length			
	<b>1800mm</b> standard length			
	<b>2400mm</b> standard length			
	<b>Specify length</b>			

\* Items available for Quickship

### Product Description

A 60mm continuous surface mounted or suspended downlight with minimal visual impact. Can be specified to any desired length.

### Lamp

T5 fluorescent  
Base: G5  
Lamp power: 14W  
Lamp lumens: 1200 lm  
Information shown based on one T5 lamp

### Power Supply

- ND: non dimming
- 1-10V: 1-10 Volt dimming, min 10%
- DALI: DALI protocol, min 10%
- DSI: Digital

### Voltage

220-240V AC 50-60Hz  
120-277V universal AC 50-60Hz

### Emergency




EMND: emergency non-dimmable  
EMST: emergency self-test  
EMDA: emergency DALI protocol

### Finish

Standard product finish is white powder coated RAL 9010 with 30% gloss.

### Note

Indicative lamp information shown. Consult lamp manufacturer for current information.



## Specifier Details