

# 4" ProTools D Downlight


## Square Flush Diffuser



Recessed Plaster Trim




Recessed Bezel Trim



Cut Out:  $\square$ 4.75" (120mm)

Recessed Plaster Trim (RPT)



Cut Out:  $\square$ 4.75" (120mm)

Recessed Bezel Trim (RBT)

### Ordering Information

WG-100SPTD					FSOD	LAM		
Model	Fixation	Power <sup>1,2</sup>	CRI/CCT	Driver <sup>4</sup>	Lens	Beam	Finish	Options
WG-100SPTD	RPT RBT	L M H	927 930 935 940	X SW D010 DALI LE	FSOD	LAM	W G	LP CP IC

### Luminaire

- 4" square aperture downlight for wide distribution ambient lighting.
- High angle distribution for good vertical illumination.
- High transmission, evenly illuminated Flush Satin Opal Lens.
- Luminaire and driver installed and maintained from below the ceiling.
- Minimum of 5.5" (127mm) ceiling void is required to install the fixture from below the ceiling (integral driver).
- Modular interchangeability throughout the entire ProTools range of products.

### Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim

### Power<sup>1,2</sup>

- L = Low Power, 5.5W @ 350mA
- M = Mid Power, 8W @ 500mA
- H = High Power, 11.4W @ 700mA

### CRI/CCT<sup>3</sup>

- 90+ CRI (Low/Medium/High Power)
- 927 = 2700K, (759/1074/1488 lm)
  - 930 = 3000K, (771/1092/1512 lm)
  - 935 = 3500K, (795/1128/1566 lm)
  - 940 = 4000K, (834/1188/1638 lm)

### Driver<sup>4</sup>

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

### Lens

- FSOD = Flush Square Satin Opal Lens

### Beam

- LAM = Lambertian

### Finish

- W = White
- G = Gray

### Options

ProTools downlights require no additional options kits for remodel & new construction

- LP = Landing Pan
- CP = Chicago Plenum Housing
- IC = IC/NC Housing

<sup>1</sup> Other lumen packages available, consult factory.

<sup>2</sup> See LED data sheet for delivered lumens.

<sup>3</sup> Wattage shown does not include power supplies/drivers. System wattage adds 10-20%.

<sup>4</sup> See power supply page for details.