

4" ProTools D Downlight


Square Regressed Cover



Recessed Plaster Trim




Recessed Bezel Trim



Cut Out: 4.75" (120mm)

Recessed Plaster Trim (RPT)



Cut Out: 4.75" (120mm)

Recessed Bezel Trim (RBT)

Ordering Information

Model	Fixation	Power ^{1,2}	CRI/CCT	Driver ⁴	Cover	Lens	Beam	Finish	Options
WG-100SPTD					SRP	RSO	110		
WG-100SPTD	RPT RBT	L M H	927 930 935 940	X SW D010 DALI LE	SRP	RSO	110	W G	LP CP IC

Luminaire

- 4" square aperture downlight with wide distribution ambient lighting.
- 0.7" regressed, evenly illuminated, highly efficient Satin Opal Lens.
- High efficiency, high transmission lens.
- Luminaire and driver installed and maintained from below the ceiling.
- Minimum of 5.5" (127mm) ceiling void is required to install the fixture from below the ceiling (integral driver).
- Modular interchangeability throughout the entire ProTools range of products.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim

Power^{1,2}

- L = Low Power, 5.5W @ 350mA
- M = Mid Power, 8W @ 500mA
- H = High Power, 11.4W @ 700mA

CRI/CCT³

- 90+ CRI (Low/Medium/High Power)
- 927 = 2700K, (759/1074/1488 lm)
 - 930 = 3000K, (771/1092/1512 lm)
 - 935 = 3500K, (795/1128/1566 lm)
 - 940 = 4000K, (834/1188/1638 lm)

Driver⁴

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

Cover

- SRP = Square Regressed Pinhole

Lens

- RSO = Regressed Satin Opal

Beam

- 110 = 110° Beam Angle

Finish

- W = White
- G = Gray

Options

ProTools downlights require no additional options kits for remodel & new construction

- LP = Landing Pan
- CP = Chicago Plenum Housing
- IC = IC/NC Housing

¹ Other lumen packages available, consult factory.

² See LED data sheet for delivered lumens.

³ Wattage shown does not include power supplies/drivers. System wattage adds 10-20%.

⁴ See power supply page for details.