



Box Cove Specifications



1.5"
38mm

5"
127mm

Architectural Cove



4" (100mm) minimum offset,
12" (305mm) typical offset

Can be installed in Cove or Coffer.

Ordering Information

Model	Fixation	Pattern	Length	Power ¹	CRI/ CCT ²	Driver ³	Lens	Finish	Options
WG-BC	SM	S ¹ PC ² PR ² PZ ²	A A x B A x B x C A x B x A x B	L M H	927 930 935 940	X SW D010 DALI LE	SSD CDC SDC	W (std) B G F	LEC REC LREC

Luminaire

- Light source positioned for optimum horizontal spread of illumination.
- Light source is not visible from any viewing angle up to and including direct horizontal view.
- Delivers continuous soft wash of directed light to above surface.
- Satin Diffuser for high efficiency and soft edge beam without striations.
- Removable light source sub assembly for simple installation and maintenance.
- High efficiency linear LED in a range of outputs.
- Lengths and angles factory cut to exact field dimensions.
- Mitered corners available with continuous illumination.

Fixation

- SM = Surface mount

Pattern

- S = Straight run¹
- PC = Standard patterns coffer 2, 3 or 4 sided with 90° corners²
- PR = Standard patterns raft 2, 3 or 4 sided with 90° corners²
- PZ = Non-standard patterns and/or corners other than 90°, consult factory²

Length

- A, B, C = specify inches to the nearest 0.25" (6.35mm), i.e. 72.25" (1835mm)
For patterns specify each length, i.e. 2 sided:
A x B = 72.25" (1835mm) x 48" (1220mm);
3 sided:
A x B x C; 4 sided: A x B x A x B)

LED³

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)
- H = 34W/m high power (24V)

CRI/CCT²

- 90+ CRI minimum (Low/Mid/High)
- 927 = 2700K, (797/1476/2200 lm/m)
 - 930 = 3000K, (823/1522/2270 lm/m)
 - 935 = 3500K, (840/1555/2316 lm/m)
 - 940 = 4000K, (850/1568/2339 lm/m)

Driver (remote)³

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

Lens

- SSD = Snap On Satin Diffuser (standard)
- CDC = Clear Dust Cover
- SDC = Satin Clear Dust Cover

Finish

- W = White finished trim, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Options

- LEC = Left end cap
- REC = Right end cap
- LREC = Left & Right end caps

Emergency

- Emergency LED driver available, order separately.

¹ Wattage shown does not include power supplies/drivers.

² Delivered lumens with Snap On Satin diffuser shown.

³ Remote power supply required. See power supply page for details.




Box Cove


Ends and Corners

whitegoods


End Caps



WG-BC-LEC
Left End Cap*



top view



WG-BC-REC:
Right End Cap*

