


20 Linear Surface Louver



Ordering Information									
Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish	Cable
WG-20LDL-SM		S					LL45B		
WG-20LDL-SM	GT9 GT15 MM SC A90 A180	S	A	L M	927 930 935 940	X S D010 L3DAE L3DOE DFPN	LL45B	W (std) B G F	C4 (std) C10 C20 C30



Luminaire

- Continuous Louver, surface mounted.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Specify housing to nearest 0.25", light insert delivered in 4.74" increments.
- Supplied with 4' class 2 plenum rated feed cable per fixture lengths.

Fixation

- GT9 = 9/16" T-bar grid clip
- GT15 = 15/16" T-bar grid clip
- MM = Magnet mounting
- SC = Screw clip
- A90 = Adjustable 90° bracket
- A180 = Adjustable 180° bracket

Pattern

- S = Straight run

Length

- A = specify inches to the nearest 0.25" (i.e. 72.25"), light insert delivered in 4.74" increments.

Power¹

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)

CRI/CCT²

- 90+ CRI (low/mid power)
- 927 = 2700K (63/117 lm/ft)
 - 930 = 3000K, (65/120 lm/ft)
 - 935 = 3500K, (66/123 lm/ft)
 - 940 = 4000K, (67/124 lm/ft)

Driver (remote)³

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1%, 120VAC

Lens

- LL45B = Linear louver black

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Cable

- C4 = 4' tray cable (plenum rated) (standard)
- C10 = 10' tray cable (plenum rated)
- C20 = 20' tray cable (plenum rated)
- C30 = 30' tray cable (plenum rated)

Emergency

- Emergency LED driver available, order separately.

¹ Wattage shown does not include power supplies/drivers.

² Delivered lumens with black louver shown.

³ Remote power supply required. See power supply page for details.