


20 Linear Under Cabinet



Ordering Information								
Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish
WG-20LUC		S		L		S		
WG-20LUC	MM CM	S	18 24 30 36 42 48	L	927 930 935 940	S	OD (std) SD	W (std) G



Total Length includes 1" for switch.
1" clearance required for cable.

Luminaire

- Under cabinet and task light.
- Standard Opal Diffuser for even illumination and no LED appearance.
- Satin Diffuser for high efficiency and minimal LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 Steps MacAdam delivering excellent color rendering.
- On / Off switch with 118" cable and plug.

Fixation

- MM = Magnetic mounting
- CM = Clip mounting

Pattern

- S = Straight run (for other product configurations see 20LDL-SM)

Length

(Total length includes 1" for switch, requires 1" clearance for cable)

- 18 = 18"
- 24 = 24"
- 30 = 30"
- 36 = 36"
- 42 = 42"
- 48 = 48"

Power¹

- L = 3.2W/ft low power (24V)

CRI/CCT²

90+ CRI minimum (Low)

- 927 = 2700K, (188 lm/ft)
- 930 = 3000K, (194 lm/ft)
- 935 = 3500K, (198 lm/ft)
- 940 = 4000K, (200 lm/ft)

Driver (remote)³

- S = Standard driver 120 - 240V, 50 - 60 Hz

Lens

- OD = Satin Opal Diffuser (standard)
- SD = Satin Clear Diffuser (high efficiency)

Finish

- W = White, 20% gloss, RAL9010 (standard)
- G = Gray, 20% gloss

Emergency

- Emergency LED driver available, order separately.

1 Wattage shown does not include power supplies/drivers.

2 Delivered lumens with satin opal diffuser shown.

3 24V fixture supplied complete with individual socket mount power supply 120-240V, 50-60 Hz and feed cable.