



# Mini Box Cove Specifications



Ordering Information									
Model	Fixation	Pattern	Length	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Driver <sup>3</sup>	Lens	Finish	Options
WG-MBC	SM	S <sup>1</sup> PC <sup>2</sup> PR <sup>2</sup> PZ <sup>2</sup>	A A x B A x B x C A x B x A x B	L M H	927 930 935 940	X SW D010 DALI LE	SSD (std) CDC SDC	W (std) B G F	LEC REC LREC



Architectural Cove  
4" (100mm) minimum offset,  
12" (305mm) typical offset  
Can be installed in Cove or Coffer.

## Luminaire

- Light source positioned for optimum horizontal spread of illumination.
- Light source is not visible from any viewing angle up to and including direct horizontal view.
- Delivers continuous soft wash of directed light to above surface.
- Satin Diffuser for high efficiency and soft edge beam without striations.
- Removable light source sub assembly for simple installation and maintenance.
- High efficiency linear LED in a range of outputs.
- Integral drivers and through wiring.
- Lengths and angles factory cut to exact field dimensions.
- Mitered corners available with continuous illumination.

## Fixation

- SM = Surface mount

## Pattern

- S = Straight run<sup>1</sup>
- PC = Standard patterns coffer 2, 3 or 4 sided with 90° corners<sup>2</sup>
- PR = Standard patterns raft 2, 3 or 4 sided with 90° corners<sup>2</sup>
- PZ = Non-standard patterns and/or corners other than 90°, consult factory<sup>2</sup>

## Length

- A, B, C = specify inches to the nearest 0.25" (6.35mm), i.e. 72.25" (1835mm)  
For patterns specify each length, i.e. 2 sided:  
A x B = 72.25" (1835mm) x 48" (1220mm);  
3 sided:  
A x B x C; 4 sided: A x B x A x B

## LED<sup>3</sup>

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)
- H = 34W/m high power (24V)

## CRI/CCT<sup>4</sup>

- 90+ CRI minimum (Low/Mid/High)
- 927 = 2700K, (797/1476/2200 lm/m)
  - 930 = 3000K, (823/1522/2270 lm/m)
  - 935 = 3500K, (840/1555/2316 lm/m)
  - 940 = 4000K, (850/1568/2339 lm/m)

## Driver (remote)<sup>5</sup>

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

## Lens

- SSD = Snap On Satin Diffuser (standard)
- CDC = Clear Dust Cover
- SDC = Satin Clear Dust Cover

## Finish

- W = White finished trim, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

## Options

- LEC = Left end cap
- REC = Right end cap
- LREC = Left & Right end caps

## Emergency

- Emergency LED driver available, order separately.

<sup>1</sup> Wattage shown does not include power supplies/drivers.

<sup>2</sup> Delivered lumens with Snap On Satin diffuser shown.

<sup>3</sup> Remote power supply required. See power supply page for details.




# Mini Box Cove


## Ends and Corners

whitegoods


### End Caps



WG-MBC-LEC  
Left End Cap\*



top view



WG-MBC-REC:  
Right End Cap\*

