



# 20 Linear Surface Round Opal Diffuser



Ordering Information									
Model	Fixation	Pattern	Length	Power <sup>1</sup>	CRI/ CCT <sup>2</sup>	Driver <sup>3</sup>	Lens	Finish	Cable
WG-20LDL-SM		S					ROD		
WG-20LDL-SM	GT9 GT15 MM SC A90 A180	S	24 36 48 60 72 84 96 Specify ≤ 96	L M	927 930 935 940	X S D010 L3DAE L3D0E DFPN	ROD	W (std) B G F	C4 (std) C10 C20 C30



## Luminaire

- Tubular design gives light in all directions, including behind the luminaire, 315° distribution.
- Delivers a soft, even spread of light.
- End-to-end mounting gives uninterrupted lighting effect.
- Available in 0.25" increments.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Supplied with 4' class 2 plenum rated feed cable per fixture lengths.

## Fixation

- GT9 = 9/16" T-bar grid clip
- GT15 = 15/16" T-bar grid clip
- MM = Magnet mounting
- SC = Screw clip
- A90 = Adjustable 90° bracket
- A180 = Adjustable 180° bracket

## Pattern

- S = Straight run (individual fixtures only, runs are made up from standalone units ≤ 96")

## Length

- 24 = 24"
- 36 = 36"
- 48 = 48"
- 60 = 60"
- 72 = 72"
- 84 = 84"
- 96 = 96"
- Specify ≤ 96"

## Power<sup>1</sup>

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)

## CRI/CCT<sup>2</sup>

90+ CRI (low/mid/high power)

- 927 = 2700K, (243/449 lm/ft)
- 930 = 3000K, (251/463 lm/ft)
- 935 = 3500K, (256/473 lm/ft)
- 940 = 4000K, (258/478 lm/ft)

## Driver (remote)<sup>3</sup>

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3D0E = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1%, 120VAC

## Lens

- ROD = Round opal diffuser

## Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

## Cable

- C4 = 4' tray cable (plenum rated) (standard)
- C10 = 10' tray cable (plenum rated)
- C20 = 20' tray cable (plenum rated)
- C30 = 30' tray cable (plenum rated)

## Emergency

- Emergency LED driver available, order separately.

<sup>1</sup> Wattage shown does not include power supplies/drivers.

<sup>2</sup> Delivered lumens with round opal diffuser shown.

<sup>3</sup> Remote power supply required. See power supply page for details.