


20 Linear Suspended Louver



Ordering Information								
WG-P20LDL	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish
WG-20LDL-S	48 (std) 96	S	Specify up to 94.8" in 4.74" increments	L M	927 930 935 940	X S D010 L3DAE L3DOE DFPN	LL45B	W (std) B G F

Luminaire

- Glare control louver for complete shielding of light source.
- Cross blade louver with integrated holographic film.
- Exact 45° cut-off.
- Available in 4.74" increments.
- End-to-end mounting gives uninterrupted lighting effect.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Powder coat painted white - RAL 9010.

Fixation

- 48 = 48" suspension cable standard
- 96 = 96" suspension cable, field-cuttable

Pattern

- S = Straight run

Length

- Specify up to 94.8" in 4.74" increments (i.e. 23.7", 37.9", 47.4", 56.9", 85.3").

Power¹

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)

CRI/CCT²

90+ CRI (Low/Mid Power)

- 927 = 2700K (63/117 lm/ft)
- 930 = 3000K, (65/120 lm/ft)
- 935 = 3500K, (66/123 lm/ft)
- 940 = 4000K, (67/124 lm/ft)

Driver (remote)³

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1%, 120VAC

Lens

- LL45B = Linear louver black

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Emergency

- Emergency LED driver available, order separately.

¹ Wattage shown does not include power supplies/drivers.

² Delivered lumens with black louver shown.

³ Remote power supply required. See power supply page for details.