




Ordering Information									
Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish	Cable
WG-20LDL-SM		S					LL45B		
WG-20LDL-SM	GT9 GT15 MM SC A90 A180	S	A	L M	927 930 935 940	X SW D010 DALI LE	LL45B	W (std) B G F	C4 (std) C10 C20 C30



Luminaire

- Continuous Louver, surface mounted.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Specify housing to nearest 0.25" (6.35mm), light insert delivered in 4.74" (120mm) increments.
- Supplied with 4' (1220mm) class 2 plenum rated feed cable per fixture lengths.

Fixation

- GT9 = 9/16" (14mm) T-bar grid clip
- GT15 = 15/16" (24mm) T-bar grid clip
- MM = Magnet mounting
- SC = Screw clip
- A90 = Adjustable 90° bracket
- A180 = Adjustable 180° bracket

Pattern

- S = Straight run

Length

- A = specify inches to the nearest 0.25" (6.35mm), 72.25" (1835mm), light insert delivered in 4.74" (120mm) increments.

Power¹

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)

CRI/CCT²

90+ CRI (low/mid power)

- 927 = 2700K (207/384 lm/m)
- 930 = 3000K, (213/394 lm/m)
- 935 = 3500K, (216/403 lm/m)
- 940 = 4000K, (219/407 lm/m)

Driver (remote)³

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

Lens

- LL45B = Linear louver black

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Cable

- C4 = 4' (1220mm) tray cable (plenum rated) (standard)
- C10 = 10' (3050mm) tray cable (plenum rated)
- C20 = 20' (7000mm) tray cable (plenum rated)
- C30 = 30' (9140mm) tray cable (plenum rated)

Emergency

- Emergency LED driver available, order separately.

¹ Wattage shown does not include power supplies/drivers.

² Delivered lumens with black louver shown.

³ Remote power supply required. See power supply page for details.

