



Ordering Information									
Model	Fixation	Pattern	Length	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Driver <sup>3</sup>	Lens	Finish	Cable
WG-20LDL-SM		S					NL16		
WG-20LDL-SM	GT9 GT15 MM SC A90 A180	S	24 36 48 60 72 84 96 Specify ≤ 96	L M	927 930 935 940	X SW D010 DALI LE	NL16	W (std) B G F	C4 (std) C10 C20 C30

### Luminaire

- Surface mounted luminaire with evenly illuminated narrow lens.
- End-to-end mounting gives uninterrupted lighting effect.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Powder coat painted white - RAL 9010.
- Supplied with 4' (1220mm) class 2 plenum rated feed cable per fixture lengths.

### Fixation

- GT9 = 9/16" (14mm) T-bar grid clip
- GT15 = 15/16" (24mm) T-bar grid clip
- MM = Magnet mounting
- SC = Screw clip
- A90 = Adjustable 90° bracket
- A180 = Adjustable 180° bracket

### Pattern

- S = Straight run (individual fixtures only, runs are made up from standalone units ≤ 96")

### Length

- 24 = 24" (610mm)
- 36 = 36" (915mm)
- 48 = 48" (1220mm)
- 60 = 60" (1525mm)
- 72 = 72" (1830mm)
- 84 = 84" (2130mm)
- 96 = 96" (2440mm)
- Specify ≤ 96" (2440mm)

### Power<sup>1</sup>

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)

### CRI/CCT<sup>2</sup>

90+ CRI (low/mid/high power)

- 927 = 2700K, (738/1361 lm/m)
- 930 = 3000K, (761/1407 lm/m)
- 935 = 3500K, (777/1433 lm/m)
- 940 = 4000K, (784/1500 lm/m)

### Driver (remote)<sup>3</sup>

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

### Lens

- NL16 = Linear narrow lens, 16 degree

### Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

### Cable

- C4 = 4' (1220mm) tray cable (plenum rated) (standard)
- C10 = 10' (3050mm) tray cable (plenum rated)
- C20 = 20' (7000mm) tray cable (plenum rated)
- C30 = 30' (9140mm) tray cable (plenum rated)

### Emergency

- Emergency LED driver available, order separately.

<sup>1</sup> Wattage shown does not include power supplies/drivers.

<sup>2</sup> Delivered lumens with narrow lens shown.

<sup>3</sup> Remote power supply required. See power supply page for details.

