



# 20 Linear Floor Wash Semi-Recessed Plaster Trim



| Ordering Information |          |         |        |                    |                          |                               |                |                        |
|----------------------|----------|---------|--------|--------------------|--------------------------|-------------------------------|----------------|------------------------|
| Model                | Fixation | Pattern | Length | Power <sup>1</sup> | CRI/CCT <sup>2</sup>     | Driver <sup>3</sup>           | Lens           | Finish                 |
| WG-20LFW             | SRPT     | S       |        |                    |                          |                               |                |                        |
| WG-20LFW             | SRPT     | S       | A      | L<br>M             | 927<br>930<br>935<br>940 | X<br>SW<br>D010<br>DALI<br>LE | OD (std)<br>SD | W (std)<br>B<br>G<br>F |



Semi Recessed Plaster Trim (SRPT)



Gypsum Wall

## Luminaire

- Continuous, evenly illuminated snap-in lens without visible LED pattern.
- Standard Opal Diffuser for even illumination and no LED appearance. Satin Diffuser for high efficiency and minimal LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Lengths factory cut to exact field dimensions.
- Powder coat painted white - RAL 9010.
- Supplied with 4' (1220mm) class 2 plenum rated feed cable per fixture lengths.

## Fixation

- SRPT = Semi Recessed Plaster Trim

## Pattern

- S = Straight run

## Length

- A = specify inches to the nearest 0.25" (6.35mm), i.e. 72.25" (1835mm)

## Power<sup>1</sup>

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)

## CRI/CCT<sup>2</sup>

- 90+ CRI minimum (Low/Mid)
- 927 = 2700K (617/1141 lm/m)
  - 930 = 3000K (636/1177 lm/m)
  - 935 = 3500K (649/1200 lm/m)
  - 940 = 4000K (656/1214 lm/m)

## Driver (remote)<sup>3</sup>

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10V/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

## Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser (high efficiency)

## Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

## Emergency

- Emergency LED driver available, order separately (remote)

1 Wattage shown does not include power supplies/drivers.  
 2 Delivered lumens with satin opal diffuser shown.  
 3 Remote power supply required. See power supply page for details.

