



## Ordering Information


Model	Fixation	Pattern <sup>1</sup>	Length	Power <sup>2</sup>	CRI/CCT <sup>3</sup>	Driver <sup>4</sup>	Lens	Finish	Options
WG-20LPF	RPT RBT RRT RGT9 RGT15	S P	A A x B A x B x C A x B x A x B	L M	927 930 935 940	X SW D010 DALI LE	OD (std) SD	W (std) B G F	BEC FEC PEC




Recessed Plaster Trim (RPT)



Recessed Bezel Trim (RBT)



Recessed Return Trim (RRT)



Recessed Grid Trim (RGT9/RGT15)

### Luminaire

- Continuous, evenly illuminated snap-in lens flush to the ceiling plane.
- Opal Diffuser for even illumination and no LED appearance. Satin diffuser for high efficiency and minimum LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Lengths and angles factory cut to exact field dimensions specified to 0.25" (6.35mm).
- Standard and custom corners.
- Supplied with 4' (1220mm) class 2 plenum rated feed cable per fixture lengths.

### Fixation

- RPT = Recessed plaster trim
- RBT = Recessed bezel trim
- RRT = Recessed return trim
- RGT9 = Recessed Grid Trim 9/16" (14mm)
- RGT15 = Recessed Grid Trim 15/16" (24mm)

### Pattern<sup>1</sup>

- S = Straight run
- P = Standard patterns 2, 3 or 4 sided with 90° corners on the same plane.

### Length

- A, B, C = specify inches to the nearest 0.25" (6.35mm), i.e. 72.25" (1835mm)  
For patterns specify each length,  
i.e. 2 sided:  
A x B = 72.25" (1835mm) x 48" (1220mm);  
3 sided:  
A x B x C; 4 sided: A x B x A x B)

### Power<sup>2</sup>

- L = 10.5W/m low power (24V)
- M = 21W/m mid power (24V)

### CRI/CCT<sup>3</sup>

- 90+ CRI (low/mid power)
- 927 = 2700K (617/1141 lm/m)
  - 930 = 3000K (636/1177 lm/m)
  - 935 = 3500K (649/1200 lm/m)
  - 940 = 4000K (656/1214 lm/m)

### Driver (remote)<sup>4</sup>

- X = Driver ordered separately
- SW = Switched/NON DIM
- D010 = 0-10/1-10V DIM
- DALI = DALI DIM
- LE = Leading-Edge DIM

### Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser (high efficiency)

### Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

### Options

- BEC = Bezel end caps
- FEC = Flat end caps
- PEC = Plaster-in end caps

### Emergency

- Emergency LED driver available, order separately.

<sup>1</sup> See pattern spec sheet.

<sup>2</sup> Wattage shown does not include power supplies/drivers.

<sup>3</sup> Delivered lumens with satin opal diffuser shown.

<sup>4</sup> Remote power supply required. See power supply page for details.

