




Ordering Information								
Model	Fixation	Pattern	Length	Power ¹	CRI/CCT ²	Driver ³	Lens	Finish
WG-20LUC		S		L		S		
WG-20LUC	MM CM	S	18 24 30 36 42 48	L	927 930 935 940	S	OD (std) SD	W (std) G



Total Length includes 1" (25mm) for switch. 1" (25mm) clearance required for cable.

Luminaire

- Under cabinet and task light.
- Standard Opal Diffuser for even illumination and no LED appearance.
- Satin Diffuser for high efficiency and minimal LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 Steps MacAdam delivering excellent color rendering.
- On / Off switch with 118" (3000mm) cable and plug.

Fixation

- MM = Magnetic mounting
- CM = Clip mounting

Pattern

- S = Straight run (for other product configurations see 20LDL-SM)

Length

(Total length includes 1" (25mm) for switch, requires 1" (25mm) clearance for cable)

- 18 = 18" (460mm)
- 24 = 24" (610mm)
- 30 = 30" (760mm)
- 36 = 36" (915mm)
- 42 = 42" (1070mm)
- 48 = 48" (1220mm)

Power¹

- L = 10.5W/m low power (24V)

CRI/CCT²

90+ CRI minimum (Low)

- 927 = 2700K (617 lm/m)
- 930 = 3000K (636 lm/m)
- 935 = 3500K (649 lm/m)
- 940 = 4000K (656 lm/m)

Driver (remote)³

- S = Standard driver 220 - 240V, 50 - 60 Hz

Lens

- OD = Satin Opal Diffuser (standard)
- SD = Satin Clear Diffuser (high efficiency)

Finish

- W = White, 20% gloss, RAL9010 (standard)
- G = Gray, 20% gloss

Emergency

- Emergency LED driver available, order separately.

- 1 Wattage shown does not include power supplies/drivers.
- 2 Delivered lumens with satin opal diffuser shown.
- 3 24V fixture supplied complete with individual socket mount power supply 120-240V, 50-60 Hz and feed cable.

