




Plaster Trim



Bezel Trim




2.9"  
74mm

3.5"  
89mm

3.2"  
81mm

Plaster Trim (RPT)




2.8"  
71mm

3.5"  
89mm

3.2"  
81mm

Bezel Trim (RBT)



2.8"  
71mm

3.5"  
89mm

3.2"  
81mm

4.76"  
121mm

Grid Trim (RGT9/RGT15)

## Ordering Information

Model	Fixation	Pattern	Length	Power <sup>2</sup>	CRI/ CCT <sup>3</sup>	Driver <sup>4</sup>	In-fill	Lens	Finish	Options
WG-ZC								SD		
WG-ZC	RPT RBT RGT9 RGT15	S <sup>1</sup> PC <sup>2</sup> PR <sup>2</sup> PZ <sup>2</sup>	A A x B A x B x C A x B x A x B	L M H	927 930 935 940	X S D010 L3DAE L3DOE DFPN	X P4 P5	SD (std)	W (std) B G F	LEC REC LREC

## Luminaire

- Linear perimeter slot system featuring plaster-in or bezel precision knife edge for clean, minimal effect.
- Suitable for 5/8" drywall ceiling.
- Lengths and angles factory cut to exact field dimensions.
- Mitered corners available with continuous LED illumination.
- Powder coat painted white - RAL 9010
- Optional adjustable In-Fill panel to accommodate 4" - 6" slot.
- Micro-refractive satin diffuser guides light further down the wall.

## Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim
- RGT9 = Recessed Grid Trim 9/16"
- RGT15 = Recessed Grid Trim 15/16"

## Pattern

- S = Straight run
- PC = Standard patterns coffer 2, 3 or 4 sided with 90° corners<sup>1</sup>
- PR = Standard patterns raft 2, 3 or 4 sided with 90° corners<sup>1</sup>
- PZ = Non-standard patterns and/or corners other than 90°, consult factory<sup>1</sup>

## Length

- A, B, C = specify inches to the nearest 0.25" (i.e. 72.25") For patterns specify each length (i.e. 2 sided: A x B = 72.25" x 48"; 3 sided: A x B x C; 4 sided: A x B x A x B)

## Power<sup>2</sup>

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)
- H = 10.5W/ft high power (24V)

## CCT / CRI<sup>3</sup>

- 90+ CRI minimum (Low/Mid/High)
- 927 = 2700K, (256/473/706 lm/ft)
  - 930 = 3000K (264/488/728 lm/ft)
  - 935 = 3500K, (270/498/743 lm/ft)
  - 940 = 4000K, (272/503/750 lm/ft)

## Driver<sup>4</sup>

- S = Standard driver, 120-277V
- D010 = 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V (remote only)
- DFPN = Lutron Forward Phase 1% 120VAC

## In-fill

- X = No in-fill panel
- P4 = 4" - 5" adjustable in-fill panel
- P5 = 5" - 6" adjustable in-fill panel

## Lens

- SD = Satin clear diffuser (standard)

## Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

## Options

- LEC = Left end cap
- REC = Right end cap
- LREC = Left & Right end caps

## Emergency

- Contact factory for emergency lighting options

<sup>1</sup> See pattern spec sheet. Standard setup assumes the cove ends at a perpendicular wall and the led board is setback from the end to minimize light on the perpendicular wall. Contact us for options.

<sup>2</sup> Wattage shown does not include power supplies/drivers.

<sup>3</sup> Delivered lumens with satin clear diffuser shown.

<sup>4</sup> Integral driver, except L3DOE (remote only). See power supply page for details.